



# arvex

## **PORCELAIN MOSAIC**

**The product may be susceptible to scratching in handling and installation, as well as use. Expect variation of color run from production to production.**

### *Cutting*

Cut mosaics with a wet saw using a diamond blade. Cut mosaics slowly using multiple passes, increasing the depth with each pass.

### *Grouting*

Apply a premium grade thin-set mortar using a 4 mm V-notch trowel for small mosaics or 6 mm Square-notch trowel for large mosaics.

Set tiles, apply pressure or tap the surfaces with a rubber grout float to ensure all tiles are bonded and aligned properly. Use a level periodically to check the grout joints.

Mix and apply grout. For mosaics tiles with a metallic glaze finish use unsanded grout to prevent surface abrasion.

Clean all excess grout immediately with a damp sponge.

After 12 hours polish any remaining grout haze with a clean dry cloth.

### *Cleaning and maintenance*

Do not use abrasive cleaners or harsh chemicals. Use all-purpose cleaner recommended and safe for use on your mosaics.

### *Usage*

Porcelain mosaic is recommended for interior walls. It can be installed on shower walls and shower floors.

### *Product inspection and claims*

Being an artistic production, there may be a few minor defects or variations in intensity, composition, tone and brightness of the color. It is recommended to inspect all the material in the sunlight before the installation.